



Protective Papers and Films

# PROTEX 55 PAPER



**ROLLS SIZES:**  
48" x 100 yds

**Protex 55** is a 4-5 mil latex saturated paper, designed for pre-spacing and application of large or small surface area decals. The tack level of the product gives proper adhesion as needed to lift the connected film from its release liner, in registration, for application to substrate. It is also used on punched stencil material (Sharpline 200) to hold letters in place for transporting and application. It may also be applied directly to bare aluminum, stainless steel or painted surfaces to protect from scratches.

*\*This product is not intended for fly-away applications. Test prior to use on copper, brass or anodized aluminum or before outdoor exposure.*

**BACKING:**

Basis wt., lbs./3,000 sq. ft. ....	35 - 40
Thickness, mils .....	3.6 - 4.4
Tensile strength, lbs./inch, M.D. ....	16.4 min.
Elongation, % M.D.....	2.5 min.
Elmendorf Tear, grams, MD .....	46 min.
CD .....	49 min.

**ADHESIVE:**

Base .....	Natural Latex
Adhesion to steel, oz./in. width.....	20 - 25 (-3/+4)
(At time of manufacture)	
PSTC-1 (Modified).....	Silicone Free

**STORAGE:**

Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

**MASK-OFF COMPANY, INC.**  
345 West Maple Ave. P.O. Box 1148  
Monrovia, CA 91016  
Main (626) 359-3261 | FAX (626) 359-7160  
[www.mask-off.com](http://www.mask-off.com)