



Protective Papers and Films

# PROTEX 8209L FILM



## ROLLS SIZES:

48" x 60 yds

48" x 100 yds

**Protex 8209L** will provide superior pressure sensitive protection as well as abrasion resistance on a large variety of surfaces while providing the flexibility to conform to complex curves. Protex 8209L has been successfully applied to the following surfaces:

Acrylic/Polycarbonate	Plastics
Sheeted/Painted Metal	Carpet
Drywall (Painted)	Vinyl
Glass	Rubber
Aluminum	Wood
Fabric	Tedlar

*\*This product is not intended for fly-away applications. Test prior to use on copper, brass or anodized aluminum or before outdoor exposure.*

### BACKING:

Basis wt., (gr./242") .....	3.4 - 3.6
Thickness, mils .....	2.6 - 3.5
Elongation, % M.D.....	110 min.

### ADHESIVE:

Base .....	Acrylic
Adhesion to steel, oz./in. width .....	6 - 14 (-1/+2)
(At time of manufacture)	
PSTC-1 (Modified) .....	Silicone Free

### HEAT RESISTANCE:

125-150° (F) .....	72 hours
200-250° (F).....	2 hours

### LINER:

Flat

### STORAGE:

Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

### MASK-OFF COMPANY, INC.

345 West Maple Ave. P.O. Box 1148

Monrovia, CA 91016

Main (626) 359-3261 | FAX (626) 359-7160

[www.mask-off.com](http://www.mask-off.com)