



MASK-OFF COMPANY

STENCIL PAPERS

PROTECTIVE PAPERS AND FILMS

SPECIALTY COATINGS

P.O. BOX 1148 * 345 WEST MAPLE AVENUE * MONROVIA, CALIFORNIA 91016 * PHONE (626) 359-3261 FAX (626) 359-7160

PROTEX 8209L

USES: Protex 8209L will provide superior pressure sensitive protection as well as abrasion resistance on a large variety of surfaces while providing the flexibility to conform to complex curves. Protex 8209L has been successfully applied to the following surfaces:

Acrylic/Polycarbonate	Plastics	Glass	Wood
Sheeted/Painted Metal	Carpet	Rubber	Fabric
Drywall (Painted)	Vinyl	Aluminum	Tedlar

HEAT RESISTANCE *(Excludes Acrylic/Plastics)* :

125-150° (F)	72 hours
200-250° (F)	2 hours

TYPICAL PROPERTIES:

BACKING:

Basis Weight (gr./24 ^{2"})	3.4-3.6
Thickness, mils	2.6-3.5
Elongation, % M.D.	110 min

ADHESIVE:

Base	Acrylic
Adhesion to steel, oz./in. width <i>(At time of manufacture)</i>	6-14 (-1/+2)
PSTC-1 (Modified)	Silicone Free

RELEASE LINER:

Flat

STORAGE:

Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.

ROLL SIZES:

48" X 60 YRDS

48" X 100 YRDS