



Protective Papers and Films

Sharpline 200

SHARPLINE 200 is a 4 - 5 mil latex saturated paper used for die-cut or hand-cut spray mask stencils and masking of surfaces to be painted. Used for sign lettering, auto pinstripping, and aircraft stenciling where paint is used instead of decals. Adhesive is formulated to withstand temperatures of 200 degrees F. to 300 degrees F. for short periods of time. The product is designed to prevent paint from bleeding through and allows for a clean sharp edge. A liner allows product to be die-cut if desired. Can be adapted for computerized stencil machines.

**This product is not intended for fly-away applications. Test prior to use on copper, brass or anodized aluminum or before outdoor exposure.*



BACKING:

Basis wt., lbs./3,000 sq. ft.	42 - 49
Thickness, mils	4 - 5
Tensile strength, lbs./inch, M.D.	12.7 min.
Elongation, % M.D.	6.0 min.
Elmendorf Tear, grams, MD	56 min.
CD	56 min.

ADHESIVE:

Base	Natural Latex
Adhesion to steel, oz./in. width <i>(At time of manufacture)</i>	24 - 30 (-4/+5)
PSTC-1 (Modified)	Silicone Free

Liner: Flat

STORAGE: Shelf life is 1 year if stored in a cool dry place, out of direct sunlight.